

CHEM LINK

Construction & Maintenance

Telephone: 800-826-1681

Fax: 269-679-4448

353 E. Lyons Street

Schoolcraft, MI 49087

www.chemlink.com

Product Description

The **ChemCurb System** replaces the old style metal pitch pans with versatile precast curb components, pourable sealant, and structural adhesive/sealant. The system can usually be installed in under 15 minutes and eliminates the need for flashing or mechanical attachment.

The **ChemCurb System** is designed for use on granulated modified bitumen, PVC, EPDM, PIB, TPO single ply, asphalt, and coal tar B.U.R. Please note TPO Primer must be used on TPO single-ply roof substrates. When installed properly, the **ChemCurb System** forms a durable waterproof rubber seal around penetrations of any size. An extended manufacture warranty against leaks is activated when **CHEM LINK** receives a completed warranty card and proof of purchase.

Special Characteristics

- Rapid installation - reduces labor significantly.
- Excellent adhesion to most roofing materials.
- No flashing or mechanical attachment required.
- Sealant is flexible down to -40°F (-40°C).
- Service Temperature -40°F to 200°F (-40°C to 93°C)
- **1-Part**® accommodates movement and is suggested for use on all granulated membranes and details with excessive movement.
- For sloped roof applications, substitute **DuraLink**® 50 non-slump adhesive/sealant for **M-1**® and **1-Part**

Restrictions

- Please contact customer service for application guidelines with temperatures below 32°F (0°C).
- Do not install if rain is anticipated within 4 hours
- Do not use on Hypalon or smooth APP modified bitumen membrane. For smooth APP, torch down a target of granulated APP before installation.
- TPO Primer must be used for TPO applications.
- Do not prime bonding surfaces with asphalt primer.
- Do not use asphalt cement as a "night sealant." Use **M-1** for this purpose.
- **ChemCurb** kits are designed to contain enough **1-Part** to fill each curb with displacement in consideration. Refer to our penetration calculator under contractor resources at chemlink.com to verify volumes

Last Revision: 7/16/20
Document No. DS1307



ChemCurb System Components

- **ChemCurb** exterior rings, straights, and corners.
- **M-1** Structural Adhesive/Sealant used for bonding the **ChemCurb** components, sealing and priming the penetration.
- **1-Part** moisture cure pourable sealer or **PRO PACK**™ two-part urethane pourable sealer. Both sealants are used to form a durable, water-tight seal around the roof penetration.

ChemCurb precast form components are composed of gray polyester resin. The **ChemCurb** is 2-inches high and is available in a variety of shapes and sizes. Bisected circular curbs have an inside diameter of 7.5 or 5 inches. Straight pieces are available in 6 and 12 inch lengths and combined with 2-inch radius corners to create larger sizes. The outer surface is impervious to ice, corrosion, UV (ultraviolet) light, and ponding water.

M-1 Structural Adhesive/Sealant is a durable, self-fixturing, moisture cure mastic. Cartridges of **M-1** are supplied in each **ChemCurb** Kit.

1-Part is a highly flexible, self-leveling moisture cure pourable sealer that eliminates mixing. It is also 100% solid rubber, has a very low VOC content, will not melt or shrink, and is resistant to deterioration. It is supplied in 10.1-oz and 28-oz cartridges or 1/2 gallon pouches. Unused sealant can be capped and reused.

US Patent No. US 5,768,838 and US RE41,586
Made in the USA - ISO 9001:2015 certified



Step 1

Remove all previously applied caulk, mastic, cement, asphalt, and other contaminants from penetrations with a wire brush. Clean all smooth substrates with isopropyl or denatured alcohol. Brush away all gravel or loose granules. Seal the base of each penetration with **M-1**. Coat penetrations with **M-1** to 3" above the roof line.



Step 2

Hold a section of **ChemCurb**, flat side up, and apply a 1/4" bead of **M-1** to the entire bottom perimeter. Apply 1 additional 1/4" bead of **M-1** down the center of the section. Do not tool the beads flat. Place the **ChemCurb** section on the roof surface to form a half circle around the penetration(s). Press down firmly until **M-1** extrudes from the outside edges.



Step 3

Apply **M-1** to the second section of **ChemCurb** as described above and to the scarf joints. Place the second section of curb on the roof surface to form a circle with the first section. Press firmly in place until excess adhesive extrudes from the outside edges. Apply a bead of **M-1** around the outside base of the installed **ChemCurb**, and tool to form a smooth fillet.



Step 4

Cut tip off **1-Part** cartridge at widest point on plastic nozzle and pierce the foil seal. Insert into caulking gun and pump **ChemCurb** full. When using a **1-Part** pouch, remove cap, pour, squeeze out excess air, and reseal.

Note: To provide an adequate rubber seal, maintain a 1" distance between penetrations and inside edge of the **ChemCurb**.



All properties described in this document are derived from testing conducted in laboratory conditions. Properties and performance will vary depending on environmental conditions and application technique. Test and evaluate to determine appropriate usage. Visit www.chemlink.com for the Safety Data Sheet, Technical Data Guides and full warranty for this product.

LIMITED WARRANTY: **CHEM LINK** warrants this product's performance, provided it is properly stored and applied within 1 year. If this **CHEM LINK** material is proved to be defective, return remaining product and purchase receipt for refund or replacement of product exclusive of labor or cost of labor. This is the sole and exclusive remedy for defects or failure of this product. User must read and follow the direction of the current Technical Data Guide and SDS prior to product use. User determines suitability of product for intended use and assumes all risks. Manufacturer shall not be liable for damages (including consequential or incidental damages) in excess of the purchase price, except where such exclusion or limitation is prohibited by state law. THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, WRITTEN OR ORAL, STATUTORY, EXPRESS OR IMPLIED INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE; except for the above express warranty given by manufacturer, the product is sold with all faults. **CHEM LINK** SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS. This warranty gives you specific legal rights, and you may also have other rights in the U.S. which vary from state to state. For warranty claim information, call 800-826-1681.