



DECLARATION OF PERFORMANCE

according to Annex III of the Regulation (EU) No 305/2011

Product Name: **M-1**

DoP-Nr. 439-19-3

1. Product classification code:

EN 15651-1:2012: F EXT-INT 20HM

EN 15651-2:2012: G 20LM

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Batch-No.: see product packaging/labeling

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Joint sealant for facades and glazing applications

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Chem Link, 353 E. Lyons Street, Schoolcraft, MI 49087

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3 plus 3

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

A notified testing laboratory, SKZ-Testing GmbH, NB 1213, has performed the determination of the product-type on the basis of Initial Type Testing (ITT) under system 3 and issued a corresponding test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance


Conditioning: procedure A

Substrate: Glass, Aluminum (anodized).

Essential Product Features	Performance	Harmonized Technical Specification
Reaction to fire (EN ISO 11925-2)	Class E	EN 15651-1:2012 EN 15651-2:2012
Release of dangerous substances	NPD	
Resistance to flow (EN ISO 7390)	≤ 3 mm	
Loss of volume (EN ISO 10563)	≤ 10 %	
Tensile properties		
Secant module at + 23 °C	≥0,4 MPa	
Secant module at - 20 °C	≥0.6 MPa	
Tensile properties under pretension (EN ISO 8340)	Passed (NF)	
Adhesion/elongation under pretension and after immersion in water (EN ISO 10590)	Passed (NF)	
Resilience (EN ISO 7389)	≥ 60%	
Artificial weathering by UV-light (EN ISO 11431)	Passed (NF)	
Determination of the resistance to pressure (EN ISO 11432)	0.8 MPA	
Adhesion/cohesion properties at variable temperature (EN ISO 9047)	Passed (NF)	
Durability	Passed	

10. The performance of the product identified in section 1 and 2 is in conformity with the performance declared in section 9. This declaration of performance is issued under the sole responsibility of the manufacturer as identified in section 4.

Signed for on behalf of Chem Link by Company Management



 Vice President