HIGH-PERFORMANCE ADHESIVES, **SEALANTS, SYSTEMS & ACCESSORIES**





M-1®

UNIVERSAL ADHESIVE/SEALANT

5 fl. oz. | 10.1 fl. oz. | 20 fl. oz. | 28 fl. oz. 2 gal. | 5 gal.

Larger packaging sizes available made to order.

- Designed for bonding and sealing a wide range of construction materials
- · Use as an emergency underwater repair, can be applied in wet conditions
- Will not attack insulation products or unfinished metals
- High tensile, shear & tear strengths with virtually no VOCs
- Meets ASTM E84, Class A and Miami-Dade approved
- Validated for ± 35% joint movement, isocyanate-free and paintable after 24 hours





SUPER-ADHESION SEALANT

10.1 fl. oz. | 20 fl. oz.

Larger packaging sizes available made to order.

- Designed for use in roofing, cementitious siding, metal architecture, curtain wall construction and joints subject to movement
- Bonds to difficult surfaces such as anodized metals and Kynar 500® PVDF coated metals
- Non-slump applies vertically overhead
- Isocyanate-free, solvent-free, 100% solids will not shrink, virtually no VOCs
- Validated for ± 50% joint movement, paintable after 24 hours





MULTI-PURPOSE SEALANT

10.1 fl. oz. | 20 fl. oz.

Larger packaging sizes available made to order.

· High-performance, economic sealant designed for uses from window seals, sealing joints in door frames, parapets, and block & masonry bonds to difficult surfaces such as Kynar 500® PVDF coated metals



- Non-slump applies vertically overhead
- Isocyanate-free, solvent-free, 100% solids will not shrink, virtually no VOCs
- Validated for ± 35% joint movement, isocyanate-free and paintable after 24 hours



Larger packaging sizes available made to order.

Premium grade, moisture-cure sealant designed for use in fenestrations, perimeter sealing (windows, doors and panels), metal architecture, curtain wall construction and joints subject to movement



- Solvent-free, 100% solids will not shrink, virtually no VOCs
- Non-slump applies vertically overhead
- Validated for ± 50% joint movement, paintable after 24 hours
- Miami-Dade approved







HIGH-PERFORMANCE SILICONE ADHESIVE/SEALANT

10.1 fl. oz. | 20 fl. oz.

Larger packaging sizes available made to order.

- May be used to seal windows, doors, curtain walls, roofing, gutters and in solar, transportation and marine applications — bonds to difficult surfaces such as Kynar 500® PVDF and Tedlar® PVF
- Neutral cure will not promote corrosion on uncoated metals
- Non-slump applies vertically overhead
- Solvent-free, 100% solids will not shrink, virtually no VOCs
- Validated for ± 50% joint movement



DURASIL® SL

HIGH-PERFORMANCE SELF-LEVELING SILICONE ADHESIVE/SEALANT

• Self-leveling silicone used in E-Curb® and ChemCurb® penetration seals, primarily used for hot pipe penetrations on low slope roof applications

- No outgassing on damp surfaces
- Neutral cure will not promote corrosion on uncoated metals
- Solvent-free, 100% solids will not shrink, virtually no VOCs



METALINK

HIGH-PERFORMANCE METAL ROOF SEALANT

10.1 fl. oz. | 20 fl. oz.

Larger packaging sizes available made to order.

- Multi-purpose, neutral-cure, silicone construction and roof sealant that bonds to difficult surfaces such as Kynar 500® PVDF and Tedlar® PVF
- Will not promote corrosion on uncoated metals
- Non-slump applies vertically overhead
- Isocyanate-free, solvent-free, 100% solids will not shrink, virtually no VOCs
- Validated for ± 50% joint movement



1-PART®

POURABLE PENETRATION SEALANT

10.1 fl. oz. | 1/2 gal.

Larger packaging sizes available made to order.

- Self-leveling, moisture-cure sealant designed for use in pitch pans and E-Curb and Chem Curb penetration seals
- · No outgassing on damp surfaces
- Solvent-free, 100% solids will not shrink, virtually no VOCs
- Extended warranties available



CLEAR

GENERAL PURPOSE SEALANT

10.1 fl. oz.

- · High-performance, moisture-cure sealant that can be used to seal a wide range of construction materials
- Will not attack insulation products or unfinished metals
- No outgassing on damp surfaces
- Solvent-free, 100% solids will not shrink, virtually no VOCs



CHEMCURB/ E-CURB

PENETRATION SEALS

See Chem Link Product Catalog for available kit options.



- Rounded corners eliminate disbonding at the sides with penetration movement
- 10-year warranty out of the box with a renewable warranty after inspection
- Multiple sizes available including straights and corners for custom configurations Systems for different roof types and applications: hot-pipe, low-slope, steep-slope, metal/pitched, and vertical penetrations

















HIGH-PERFORMANCE ADHESIVES, **SEALANTS, SYSTEMS & ACCESSORIES**





M-1® CR

CLEAN ROOM CERTIFIED ADHESIVE/SEALANT

10.1 fl. oz.



No outgassing on damp surfaces

• Solvent-free, virtually no VOCs, validated for ± 25% joint movement





MOISTURE-CURE ADHESIVE/SEALANT 10.1 fl. oz.

• Designed for applications above the water line or after curing below the water line and in areas where solvent based materials are not tolerated

• Isocyanate-free, solvent-free, 100% solids — will not shrink

No outgassing on damp surfaces





JOINT SEALANT

10.1 fl. oz. | 20 fl. oz.

Larger packaging sizes available made to order.

· Moisture-cure joint sealant designed for application in damp, dry or cold climates



Will not stain absorbent stone substrates like limestone or marble

No outgassing on damp surfaces

Solvent-free, 100% solids — will not shrink, virtually no VOCs

Validated for ± 35% joint movement







TEXTURIZED ELASTOMERIC SEALANT

10.1 fl. oz.

Larger packaging sizes available made to order.

· Moisture-cure joint sealant designed for application in damp, dry or cold climates

Textured appearance compliments rough surfaces

No outgassing on damp surfaces

No primer required for most construction materials

Isocyanate-free, solvent-free, 100% solids — will not shrink, virtually no VOCs

Validated for ± 35% joint movement, paintable after 24 hours





SELF-LEVELING SEALANT

28 fl. oz. | 2 liter

Larger packaging sizes available made to order.

• Moisture-cure sealant designed for application on horizontal joints in concrete construction such as driveways, sidewalks, plaza decks, balconies, stairwells, parking structures, roof decks, and surrounding fountains and swimming pools

No outgassing on damp surfaces

Will not stain absorbent stone substrates like limestone or marble

• Solvent-free, 100% solids — will not shrink, virtually no VOCs

• Validated for ± 25% joint movement, paintable after 24 hours





NOVALINK® FP

WATERPROOFING MASTIC

10.1 fl. oz.

 Moisture-cure, high-quality, waterproofing mastic designed to fill, seal and level grout lines, voids, seams and surface damage on construction materials prior to application of liquid waterproofing



Solvent-free, 100% solids — will not shrink, virtually no VOCs







HIGH-PERFORMANCE WALL & BLOCK ADHESIVE

10.1 fl. oz. | 28 fl. oz.

A moisture-cure, fast-setting adhesive with excellent adhesion to drywall, wood, metal, concrete, landscape blocks, capstones and other masonry substrates



No outgassing on damp surfaces

Solvent-free, 100% solids - will not shrink, paintable after 24 hours





MULTI-PURPOSE CONSTRUCTION ADHESIVE

10.1 fl. oz. | 20 fl. oz. | 28 fl. oz.

Larger packaging sizes available made to order.

 Moisture-cure, fast-setting, non-burning structural adhesive designed for various "panel on frame" assemblies in commercial and residential construction

• Complies with all OSHA, State, Local and Federal air quality regulations, HUD UM-60 and ASTM D3498 specifications for bonding sub-floor construction

• Solvent-free, 100% solids — will not shrink, virtually no VOCs

· No fumes, non-toxic and non-flammable





TILESECURE

ROOF TILE ADHESIVE


FLOORSECURE™

TILE ADHESIVE

2 gal. | 5 gal.

MULTI-PURPOSE WOOD &


10.1 fl. oz.



Will not crack in extreme cold or slump due to softening, high temperatures

• Solvent-free, 100% solids — will not shrink, virtually no VOCs, paintable after 24 hours

• No fumes, non-toxic and non-flammable





No outgassing on damp surfaces

Solvent-free, 100% solids - will not shrink, virtually no VOCs






NOVALINK® WM

LIQUID WATERPROOFING **MEMBRANE**

2 gal. | 5 gal.





• No outgassing on damp surfaces, non-flammable with very low odor

• Solvent-free, 100% solids — will not shrink, virtually no VOCs









